

# INSTALLATION INSTRUCTIONS



## NEW DIAMOND PRO PRODUCT!

# CLAY BRICKS

### PITCHER'S MOUND



**STEP 1:** Carefully measure out the pitcher's mound using the recommended dimensions.



**STEP 2:** Cut out and remove all loose dirt from the high stress area surrounding the pitcher's mound to a depth of 3".



**STEP 3:** Place DIAMOND PRO<sup>®</sup> Mound/Home Plate Clay BRICKS as evenly and close together as possible.



**STEP 4:** Once the BRICKS have been placed, water the cut area. Tamp the BRICKS into place.



**STEP 5:** Fill in the 1/2" remaining area with either the cut out loose material or with DIAMOND PRO<sup>®</sup> Mound/Home Plate Clay for the ideal surface.



**STEP 6:** Level and compact the new surface. Add DIAMOND PRO<sup>®</sup> Infield Conditioner to the finished area for a professional quality playing surface.

### CATCHER'S & BATTER'S BOX



**STEP 1:** Carefully measure out the catcher's and batter's box using the recommended dimensions.



**STEP 2:** Cut out and remove all loose dirt from the high stress area surrounding the pitcher's mound to a depth of 3".



**STEP 3:** Place DIAMOND PRO<sup>®</sup> Mound/Home Plate Clay BRICKS as evenly and close together as possible.



**STEP 4:** Once the BRICKS have been placed, water the cut area. Tamp the BRICKS into place.



**STEP 5:** Fill in the 1/2" remaining area with either the cut out loose material or with DIAMOND PRO<sup>®</sup> Mound/Home Plate Clay for the ideal surface.



**STEP 6:** Level and compact the new surface. Add DIAMOND PRO<sup>®</sup> Infield Conditioner to the finished area for a professional quality playing surface.